

Product Code: A2-DLM922
Features & Applications


- UK Patent GB2426321
- Integrated intumescent material completely seals the downlight and cut-out in the event of a fire
- Suitable for 30, 60 & 90 minute fire rated ceilings
- Tested to BS476 Part 21
- Tested to BS EN ISO 140-3:1995 & BS EN ISO 140-6:1998 (Acoustics) confirming that they maintain the ability for an internal or separating floor to provide sound insulation
- Includes 50W MR16 or GU10 Aluminium reflector lamp (excluding A2-DLM924/A2-DLM963)
- A2-DLM924/A2-DLM963 Low energy 11W Compact Fluorescent downlight to help meet Building Regulations Document L1A, conservation of fuel & power
- Reduced height fire rated can allows installation in shallow ceiling voids
- 2 Year guarantee

Full Description

240V GU10 Cast Aluminium Adjustable Chamfered Edge Downlight Fire Protection


Approvals

Photometric Data
Beam Cone

Polar Curve

Light Effect

Specifications

Cut Out Dia.	75 mm
Overall Dia	90 mm
Material	Cast Aluminium
Lamp Type	GU10
Guarantee	2 Years
Positional Adjustment	Adjustable
Recess Depth	115 mm
Horizontal Adjust	30 degs.
Input Voltage	240V V
Lamps Included	Yes
Dimmable	Yes

Colours

SKU Code	Colour	Lumens	Lux	MCD	Candelas	Max Watts	Colour Temp
A2-DLM922PB	Polished Brass	n/a	n/a	n/a	n/a	50.0 W	n/a
A2-DLM922PC	Polished Chrome	n/a	n/a	n/a	n/a	50.0 W	n/a
A2-DLM922SN	Satin Nickel	n/a	n/a	n/a	n/a	50.0 W	n/a
A2-DLM922SS	Satin Silver	n/a	n/a	n/a	n/a	50.0 W	n/a
A2-DLM922W	White	n/a	n/a	n/a	n/a	50.0 W	n/a

'Passionate about Lighting'